Brush Weatherguard 2A Weld On Installation & Drill On Installation Standard Available in 1" and 2" When ordering please specify the brand and dimensions of the dockboard. 1 1/2" Some models do not use any rear seal. Some use a 2" x 3" rectangular foam seal with a 1/4" diameter steel placement rod. Other models use a 1" diameter round neoprene piece with "S" hooks on each end. **Corrosion Resistant Steel** "C" Channel **Nylon Brush** Inser Extruded Aluminum **CURB ANGLE** Strip WELD ON INSTALLATION Mounting Screws DOCK LEVELER DRILL ON INSTALLATION **Brush Weatherguard**

- Brush Weatherguard can be used with any pit type dock leveler.
- **Brush Weatherguard** is an added dimension of protection for curb angles and dock boards. Two different design options of weld on or drill on can be specified for curb angle and dock board installations.
- Brush Weatherguard's snug fitting construction keeps mother nature where you want it.
- Brush Weatherguard's minimal investment provides maximum returns.

Brush Weatherguard's unique design allows you to change the brush insert with simple tools.

Brush Weatherguard consists of a nylon brush with a steel backing. It is assembled into an aluminum mounting channel which can either be screwed to the dockleveler or slid into a steel channel which can be tack welded to either the dockleveler or the curb angle. Compressible rear seals are available for certain maeks of docklevelers.

Installation procedure is simple:

Drill on Brush Weatherquard

- a. Secure the aluminum mounting strip to the dock board by drilling and attaching with screws. (Not supplied).
 b. Slide the brush seal into position and trim to required length.
- c. Install rear seal.

Brush Weatherguard ...

- reduces heating and air conditioning costs
- helps keep rodents out
- helps keep dock leveler pits clean
- is easy to install and replace
- is energy conscious